



Thermal Insulation



Flame Retardant



Termite Retardant

GREENCLAD EIFS

Exterior Insulation Finishing Systems

- Greenclad is Codemark Certified as a fully intergrated Building System in compliance with the Building Code of Australia (Volume 2 Class 1 & Class 10 residential buildings)
- Certified Wind Ratings of N1 to N5 and C1 to C2 at stud space of 600mm with cost savings over other systems

R Values of GreenClad system uncoated and coated panels

GreenClad EPS EPS Panel Thickness	Thermal Conductivity at 23c— W/mk	'R' Value at 23c - m2.K/W Uncoated Panel	'R' Value at 23c— m2.K/W Finished & Coated Panel
50mm	0.0380	1.33	1.76
75mm	0.0380	2.00	2.46
100mm	0.0380	2.67	3.11

WARRANTY: Enviroclad warrants to the purchaser of the product and the last purchaser prior to the installation of the product for a period of 10 years from the date of purchase on the sheet component of the product due to defective factory workmanship and against cracking, rotting, damage from termite attack. The render component carries a 7 year warranty against faulty product in accordance with the Painttex warranty terms and conditions. The warranty excludes faulty workmanship by the installer of the product and all installation must be carried out in accordance with the Painttex installation manual. Enviroclad reserves the right to inspect and approve the replacement of faulty product. The warranty does not cover the removal or re-installation of product deemed by Enviroclad Australia Pty Ltd to be faulty

